

875 749 HDMI 4K Matrix Switcher 4/4

Technical	
HDMI Compliant	HDCP 2.0b
HDCP Compliant	HDCP 2.2 / 1.x
Video Bandwidth	594MHz / 18Gbps
Video Resolution	480i ~ 1080p 50/60Hz, 4Kx2K@24/30Hz, 4K2K@60Hz
Color Space	RGB, YCbCr 4:4:4 / 4:2:2. YUV 4:2:0
Color Depth	8-bit, 10-bit, 12-bit (1080p@60Hz) 8-bit (4K2K@60Hz YUV4:4:4) 8-bit, 10-bit, 12-bit (4K2K@60Hz YCbCr 4:2:2 / 4:2:0)
HDMI Audio Formats	LPCM 7.1CH, Dolby TrueHD, and DTS-HD Master Audio
ESD Protection	Human-body Model: ±8kV (Air-gap discharge) , ±4kV (Contact discharge)
Connection	
Inputs	4×HDMI Type A [19-pin female] 1×IR Receiver Window 1×Micro USB
Outputs	4×HDMI Type A [19-pin female]
Mechanical	
Housing	Metal Enclosure
Color	Black
Dimensions	220mm(W)×105mm(D)×19mm(H)
Weight	535g
Power Supply	Input: AC100~240V 50/60Hz Output: DC 12V/2.5A(US/EU standard, CE/FCC/UL certified)
Power Consumption	11.04W
Operating Temperature	0°C ~ 40°C / 32°F ~ 104°F
Storage Temperature	-20°C ~ 60°C / -4°F ~ 140°
Relative Humidity	20~90% RH (non-condensing)